



Features
Fanless 4U-Rackserver with ATX-Mainboard

- Fanless Power Supply
- Chipset 945GT/ICH7R
- Integrated Intel® GMA950 Graphics
- 6 x USB 2.0 / Firewire




- Dual Gigabit LAN
- SATA II ports by ICH7R
SATA 1-4 supports
RAID 0/1/0+1/5
- 7.1 Audio (ALC880)
- PCIe x16, PCIe x1 & PCI Slots

Options:

- Redundant power supply
- 24/48 VDC input
- Hot-plug



Specification

- ATX-Motherboard for Intel® Core™Duo / Core™2 Duo Mobile CPU's (up to 2.7 GHz)
- **RAM** Dual DDR-II 533/667 MHz, non-ECC, unbuffered (240 pin DIMM) up to 4 GB
- **Expansion** : 1x PCIe x16, 1x PCIe x1, 2x PCI (up to 4x PCI (32 Bit) Slots with Extender Board)
- **Graphics** : Integrated Intel® GMA950
- **Intel® ICH7R South Bridge:**
1x UltraDMA 100/66/33, 2 x SATA
- **Audio:** Realtek ALC 880, 8ch High-Definition Audio CODEC (Dolby Master Studio, Dolby Prologic IIX, Dolby Headphone, Dolby Virtual Speaker, Dolby Digital Live)
- Two PCIe LAN: Intel 82573L GB Ethernet 
- **Internal I/O Connector:** 1x DVI+VGA, 4x USB, 1x IEEE 1394, 2x RJ45 GBLAN, 1x PS/2 Keyboard, 1x PS/2 Mouse, 1x S-Video + RCA, 1x 8 channel Audio I/O
- **On-Board Pinheaders:** 2x USB, 1 x IEEE 1394, 2 x USB, 1x IrDA
- **Environmental**
Temperature : 0- 50 Degree C
Humidity : 5 ... 95% noncondensing
- **Fanless Power Supply**
110 - 240 VAC or 12 / 24 VDC
- **Mechanical**
3 x 5 ¼" Drive Bays
1 x 3 ½" Drive Bay
2 Front Fans (Optional)
- **Dimensions** : 483 x 176 x 465 mm
- **Approval** : FCC, CE